

# Confidential for internal only

Output Power (W)	+12V (V)	+5V (V)	+3.3V (V)	-12V (V)	5VSB (V)	efficiency at 115VAC (%)	PF	efficiency at 230VAC (%)
24	12.107	4.969	3.355	-11.958	5.036	68.69	0.544	66.44
50	12.107	4.966	3.352	-11.939	5.023	76.55	0.939	74.08
100	12.105	4.966	3.352	-11.940	5.020	81.15	0.957	80.85
150	12.102	4.965	3.350	-11.944	5.015	84.67	0.967	86.62
200	12.102	4.963	3.348	-11.945	5.012	88.21	0.974	89.98
250	12.099	4.963	3.346	-11.946	5.009	90.29	0.980	91.16
300	12.099	4.960	3.342	-11.951	5.003	91.39	0.983	91.84
350	12.097	4.960	3.342	-11.953	4.999	91.99	0.986	92.23
400	12.097	4.957	3.340	-11.954	4.996	92.28	0.989	92.48
450	12.097	4.956	3.339	-11.955	4.992	92.40	0.990	92.53
500	12.094	4.955	3.338	-11.958	4.991	92.42	0.991	92.61
550	12.094	4.954	3.335	-11.959	4.986	92.36	0.992	92.58
600	12.092	4.954	3.336	-11.959	4.983	92.33	0.994	92.71
650	12.094	4.954	3.335	-11.961	4.981	92.26	0.995	92.69
700	12.092	4.954	3.335	-11.966	4.977	92.12	0.996	92.67
750	12.090	4.952	3.335	-11.967	4.974	91.97	0.997	92.65
800	12.090	4.952	3.334	-11.971	4.969	91.79	0.997	92.57
850	12.087	4.954	3.334	-11.970	4.965	91.57	0.997	92.45
900	12.085	4.952	3.332	-11.970	4.964	91.32	0.997	92.33
950	12.085	4.952	3.332	-11.972	4.957	91.10	0.998	92.19
1000	12.082	4.951	3.332	-11.974	4.956	90.86	0.998	92.08
1050	12.082	4.951	3.332	-11.977	4.952	90.51	0.998	91.92
1100	12.080	4.951	3.332	-11.979	4.949	90.23	0.998	91.73
1150	12.077	4.950	3.332	-11.980	4.945	89.91	0.998	91.57
1200	12.080	4.950	3.331	-11.981	4.943	89.62	0.999	91.41
1300	12.075	4.950	3.331	-11.983	4.939	-	0.999	91.15
1400	12.072	4.949	3.331	-11.984	4.932	-	0.999	90.77
1440	12.072	4.949	3.330	-11.988	4.926	-	0.999	90.36
电压最大偏差(%)	0.89	-1.00	1.67	1.85	-1.14	-	平均效率	90.66
负载调整率(%)	0.25	0.38	0.73	-0.35	1.86	-	OPP保护	1475